

SKIVED PTFE SHEET

.001" to .250" thick

Thickness, Tolerances and Weight Per Square Foot

| Thickness (Inches) | Tolerance +/- (Inches) | Lbs. Per Square Foot (12" x 12") |
|-----------------------|---------------------------|--|
| .001 | .0003 | .012 |
| .002 | .0003 | .024 |
| .003 | .0005 | .036 |
| .004 | .0005 | .048 |
| .005 | .0005 | .060 |
| .010 | .001 | .120 |
| .015 | .001 | .180 |
| .020 | .0015 | .240 |
| .025 | .0015 | .300 |
| .032 | .002 | .360 |
| .062 | .005 | .720 |
| .093 | .005 | 1.120 |
| .125 | .010 | 1.500 |
| .187 | .015 | 2.250 |
| .250 | .020 | 3.000 |

Standard Widths

12", 24", 36", 48"
Up to 72" wide


Material Types:

Virgin, Reprocessed,
Enflon® (filled PTFE),
Virgin & Filled Modified PTFE

**Consult sales office
for additional information.**

Etching

Sodium-Ammonia Etching available
for adhering PTFE to another surface.
Etched one-side or two-sides.



Skived PTFE Sheet



Molded PTFE Cylinder



Molded PTFE Rod



Skived PTFE Tape



Pressure Sensitive PTFE Tape



Extruded PTFE Tubing



Extruded PTFE Rod



Molded PTFE Sheet



Enflon® Filled PTFE

