

GG SERIES GAUGES AND GAUGE GUARDS



GAUGE GUARD ONLY - NO GAUGE INSTALLED

All Gauge Guards have an FPM diaphragm and are rated to 150 PSI at 70 °F.

| SIZE | MATERIAL | PART NO. |
|-------------|----------|-----------|
| 1/4" X 1/4" | PVC | GG125X25 |
| 1/4" X 1/2" | PVC | GG125X50 |
| 1/4" X 1/4" | CPVC | GG225X25 |
| 1/4" x 1/2" | CPVC | GG225X50 |
| 1/4" x 1/4" | PP | GG3025X25 |
| 1/4" x 1/2" | PVDF | GG5025X50 |



GAUGE GUARD WITH STANDARD GAUGE* INSTALLED

| SIZE | MATERIAL | GAUGE | PART NO. |
|-------------|----------|--------------|-------------|
| 1/4" X 1/4" | PVC | 0 to 30 PSI | GG125X25030 |
| 1/4" X 1/4" | PVC | 0 to 60 PSI | GG125X25060 |
| 1/4" X 1/4" | PVC | 0 to 160 PSI | GG125X25160 |
| 1/4" x 1/2" | PVC | 0 to 30 PSI | GG125X50030 |
| 1/4" x 1/2" | PVC | 0 to 60 PSI | GG125X50060 |
| 1/4" x 1/2" | PVC | 0 to 160 PSI | GG125X50160 |
| 1/4" X 1/4" | CPVC | 0 to 30 PSI | GG225X25030 |
| 1/4" X 1/4" | CPVC | 0 to 60 PSI | GG225X25060 |
| 1/4" X 1/4" | CPVC | 0 to 160 PSI | GG225X25160 |
| 1/4" x 1/2" | CPVC | 0 to 30 PSI | GG225X50030 |
| 1/4" x 1/2" | CPVC | 0 to 60 PSI | GG225X50060 |
| 1/4" x 1/2" | CPVC | 0 to 160 PSI | GG225X50160 |
| 1/4" X 1/4" | PP | 0 to 30 PSI | GG303025 |
| 1/4" X 1/4" | PP | 0 to 60 PSI | GG306025 |
| 1/4" X 1/4" | PP | 0 to 160 PSI | GG316025 |
| 1/4" X 1/2" | PVDF | 0 to 160 PSI | GG516050 |

* Shipped assembled: Gauge (not liquid-filled) is attached to Guard which is filled with hydraulic fluid.

STANDARD GAUGES ONLY

Gauges are dual faced (PSI & kg/cm²) and are available in three different PSI ratings.



| SIZE | GAUGE | PART NO. |
|------|--------------|-----------|
| 2" | 0 to 30 PSI | GG030DUAL |
| 2" | 0 to 60 PSI | GG060DUAL |
| 2" | 0 to 160 PSI | GG160DUAL |



GAUGE GUARD W/STAINLESS STEEL LIQUID FILLED GAUGE* INSTALLED

| SIZE | MATERIAL | GAUGE | PART NO. |
|-------------|----------|--------------|---------------|
| 1/4" X 1/4" | PVC | 0 to 160 PSI | GG125X25160SL |
| 1/4" X 1/2" | PVC | 0 to 160 PSI | GG125X50160SL |
| 1/4" X 1/4" | CPVC | 0 to 160 PSI | GG225X25160SL |
| 1/4" x 1/2" | CPVC | 0 to 160 PSI | GG225X50160SL |
| 1/4" x 1/4" | PP | 0 to 160 PSI | GG316025SL |
| 1/4" x 1/2" | PVDF | 0 to 160 PSI | GG516050SL |

* Shipped assembled: Gauge (Glycerin-filled) is attached to Guard (filled with hydraulic fluid).



STAINLESS STEEL LIQUID FILLED GAUGES ONLY

Gauge has stainless steel housing and is liquid-filled. Gauge face shows dual rating of PSI and kg/cm². Available in 160 PSI only.

| SIZE | GAUGE | PART NO. |
|--------|--------------|---------------|
| 2-1/2" | 0 to 160 PSI | GG160DUALFILL |



GA SERIES PRESSURE GAUGE

One-piece molded body (no assembly). Heavy duty design; simple to install.

| MATERIAL | PSI | PART NO. |
|----------|-----|-----------|
| PP | 60 | GA305060 |
| PP | 100 | GA3050100 |
| PP | 160 | GA3050160 |
| PVDF | 60 | GA505060 |
| PVDF | 100 | GA5050100 |



GDS SERIES DOUBLE SIDED PRESSURE GAUGE

Allows for easy monitoring in tight spots.

| MATERIAL | PSI | PART NO. |
|----------|-----|------------|
| PP | 60 | GDS305060 |
| PP | 100 | GDS3050100 |
| PP | 160 | GDS3050160 |
| PVDF | 60 | GDS505060 |
| PVDF | 100 | GDS5050100 |
| PVDF | 160 | GDS5050160 |



GD SERIES DIGITAL LED PRESSURE ALARM

Indicating Pressure Transmitter, bright LED display that changes colors to indicate alarm condition. Two 3A relays and one analog output. NEMA 4X, 24 VDC powered.

| CABLE | OUTPUT | PART NO. |
|-------|--------|----------|
| 2M | 4-20mA | GD132N22 |

* Includes Isolator



GLD SERIES LED PRESSURE GAUGE

All Thermoplastic Construction (Gauge + Isolator). Heavy Duty One-Piece Molded Design (No Assembly Required).

LED DISPLAY, 24 VDC POWERED, 2 X OC + 4-20 MA

| MATERIAL | PART NO. |
|----------|-----------|
| PP | GLD3050LE |
| PVDF | GLD5050LE |