

Contact details	Company:	Activity:
	Adresse:	
	Contact:	Function:
	Tel:	
	E-mail:	

Operational parameters	Flow rate (m ³ /h)	Preselection:
	Pressure (Pa)	Nature of gases:
	Direct drive: <input type="checkbox"/>	Orientation:
	Pulley/belt transmission: <input type="checkbox"/>	
	Variable frequency drive: <input type="checkbox"/>	
	Temperatures:	
	Gases: °C Normal	Ambient: °C Normal
	°C Minimum	°C Minimum
	°C Maximum	°C Maximum

Alimentation	Network tension:	Maximum sound level at 1m: (dBA)
	230V triphase <input type="checkbox"/>	Acoustic box:
	660V triphase <input type="checkbox"/>	Indoor <input type="checkbox"/> Outdoor <input type="checkbox"/>
	Frequency 60Hz <input type="checkbox"/>	Explosion proof:
Other: <input type="checkbox"/>	Gases: Ambient:	

Accessories	Vibration absorbers: <input type="checkbox"/>	Flexible sleeve on the inlet: <input type="checkbox"/>
	Access door: <input type="checkbox"/>	Flexible sleeve on the outlet: <input type="checkbox"/>
	Splinter guard: <input type="checkbox"/>	Transition square to circle on outlet: <input type="checkbox"/>
	Other: <input type="checkbox"/>	

Complementary information	
---------------------------	--