

PIPE FITTINGS

SUPER CLAMPS

FEATURES

- Stainless steel construction
- 304 stainless steel bolt with 316 stainless steel nut to prevent seizing
- 360° sealing surface
- Ideal for high torque applications
- Strong, positive connections where ordinary hose clamps fail
- T-bolt design
- 3 spot welds for extra strength
- Sold in bags of 10 only
- Torque specifications: working torque 50-80 inch pounds, maximum torque 125 inch pounds



SUPER CLAMPS

| PART NO | DESCRIPTION | MIN-MAX DIAMETER | MAX TORQUE | QTY |
|---------|-----------------------|------------------|------------|--------|
| TC120 | 1" T-BOLT HOSE CLAMP | 1.20"-1.34" | 75 IN-LBS | 10/BAG |
| TC130 | 1¼" T-BOLT HOSE CLAMP | 1.30"-1.70" | 75 IN-LBS | 10/BAG |
| TC150 | 1½" T-BOLT HOSE CLAMP | 1.50"-1.75" | 125 IN-LBS | 10/BAG |
| TC162 | 1¾" T-BOLT HOSE CLAMP | 1.62"-1.87" | 125 IN-LBS | 10/BAG |
| TC181 | 1½" T-BOLT HOSE CLAMP | 1.81"-2.06" | 125 IN-LBS | 10/BAG |
| TC193 | 1½" T-BOLT HOSE CLAMP | 1.93"-2.18" | 125 IN-LBS | 10/BAG |
| TC206 | 2" T-BOLT HOSE CLAMP | 2.06"-2.40" | 125 IN-LBS | 10/BAG |
| TC218 | 2" T-BOLT HOSE CLAMP | 2.18"-2.50" | 125 IN-LBS | 10/BAG |
| TC224 | 2" T-BOLT HOSE CLAMP | 2.24"-2.55" | 125 IN-LBS | 10/BAG |
| TC231 | 2" T-BOLT HOSE CLAMP | 2.31"-2.62" | 125 IN-LBS | 10/BAG |
| TC250 | 2" T-BOLT HOSE CLAMP | 2.50"-2.81" | 125 IN-LBS | 10/BAG |
| TC287 | 2" T-BOLT HOSE CLAMP | 2.87"-3.18" | 125 IN-LBS | 10/BAG |
| TC312 | 3" T-BOLT HOSE CLAMP | 3.12"-3.49" | 125 IN-LBS | 10/BAG |
| TC331 | 3" T-BOLT HOSE CLAMP | 3.31"-3.62" | 125 IN-LBS | 10/BAG |
| TC343 | 3" T-BOLT HOSE CLAMP | 3.50"-3.82" | 125 IN-LBS | 10/BAG |
| TC425 | 4" T-BOLT HOSE CLAMP | 4.25"-4.56" | 125 IN-LBS | 10/BAG |
| TC438 | 4" T-BOLT HOSE CLAMP | 4.38"-4.76" | 125 IN-LBS | 10/BAG |
| TC456 | 4" T-BOLT HOSE CLAMP | 4.56"-4.94" | 125 IN-LBS | 10/BAG |

TWO BARREL CLAMPS

FEATURES

- Perfect for tight, hard to reach spaces
- Minimizes parts that protrude by tightening together versus tightening away from
- Deep socket tools not required
- 300 stainless steel construction



TWO BARREL CLAMPS

| PART NO | DESCRIPTION | MIN-MAX DIAMETER | MAX TORQUE | QTY |
|---------|---|------------------|------------|-----|
| BC090 | ¾" 300 SS FLOATING BRIDGE W/LOCK WASHER | 0.91"-0.98" | 75 IN-LBS | 1 |
| BC114 | 1" 300 SS FLOATING BRIDGE W/LOCK WASHER | 1.14"-1.22" | 75 IN-LBS | 1 |